

Round pump



- ▶ Energy efficient due to the COAX® technology
- ▶ High vacuum flow with 6x COAX® Si MIDI cartridges
- ▶ Small, compact and light in weight
- ▶ Easy to mount and install in a vacuum line
- ▶ Integrated hose connectors

Technical data

Description	Unit	Value
Feed pressure, max.	MPa	0.7
Noise level	dBa	70–82
Material		PPS, PA, NBR, Viton®, SS
Temperature range	°C	-10–80
Weight	g	1130

Vacuum flow

Feed pressure MPa	Air consumption NI/s	Vacuum flow (NI/s) at different vacuum levels (-kPa)								Max vacuum -kPa
		0	10	20	30	40	50	60	70	
0.40	7.5	30.0	17.4	11.4	7.2	4.8	2.4	0.6	—	60
0.50	9.0	34.2	19.8	13.2	8.4	5.1	3.72	2.1	1.08	70
0.60	10.5	36.0	21.0	15.6	10.2	5.4	3.6	3.0	2.1	75

Evacuation time

Feed pressure MPa	Air consumption NI/s	Evacuation time (s/l) to reach different vacuum levels (-kPa)							Max vacuum -kPa
		10	20	30	40	50	60	70	
0.40	7.5	0.005	0.012	0.023	0.040	0.070	0.167	—	60
0.50	9.0	0.003	0.010	0.018	0.035	0.058	0.100	0.167	70
0.60	10.5	0.003	0.008	0.017	0.030	0.055	0.088	0.133	75

Ordering information

Description	Art. No.
Round pump COAX® 6xSi32-3	0121632

